



AMIBIND™

Unmodified Asphalt

AMIBIND™ unmodified asphalt is a performance-grade (PG) binder often used for hot mix asphalt production. As a neat asphalt, (containing no polymer modifiers) it provides a reliable balance of stiffness and flexibility, making it ideal for a wide range of paving applications. AMIBIND binders are engineered to resist rutting at high temperatures and cracking at low ones, delivering consistency, quality and performance.

Quick Facts

- Designed for hot mix production
- Improves durability
- Cost effective option
- Withstands heavy traffic
- Versatile applications
- Enables efficient paving
- Performs reliably in a wide range of climates
- Compatible with reclaimed asphalt pavement (RAP)

MORE AMI PRODUCTS




Frequently Asked Questions

Why choose AMIBIND™ for hot mix applications?

AMIBIND unmodified asphalt is a neat, performance-graded asphalt binder selected to meet your project's unique climate and traffic needs, ensuring the right balance of stiffness and flexibility. When combined with a carefully selected aggregate blend in a laboratory-designed mix, AMIBIND becomes the foundation of durable, cost-effective HMA suitable for highways, parking lots or municipal roads.

How does Asphalt Materials support customers using AMIBIND™ in the field?

In our experience, the most successful projects have a combination of quality products, trusted relationships and a team eager to be your boots on the ground. AMI provides hands-on support from experienced field teams who assist with mix design, troubleshooting and performance optimization ensuring every project gets the attention it deserves.



Interested in AMIBIND for your next paving project?

Reach out to your AMI representative or email marketing@asphalt-materials.com to discuss an evaluation.