



AMIBOND™

Tack Coat

AMIBOND™ tack coat and non-tracking tack coat are light applications of asphalt emulsion sprayed onto an existing pavement surface before placing a new layer of hot mix asphalt. Their primary purpose is to ensure a strong bond between pavement layers, preventing slippage or delamination caused by traffic loads and environmental conditions. This bonding layer is essential for the structural integrity and longevity of asphalt pavements.

Quick Facts

- Improves bonding between layers
- Enhances pavement durability
- Reduces surface failures
- Prevents slippage, debonding and delamination
- Minimizes cracking and rutting
- Quick and efficient application



Frequently Asked Questions


When should I consider a non-tracking tack coat?

Non-tracking tack coats offer a clean, efficient application that sets quickly and stays in place. This allows for faster return to traffic, improved job site cleanliness and consistent bonding performance, making them ideal for high-traffic or time-sensitive paving projects.

How does Asphalt Materials support customers using AMIBOND™ in the field?

In our experience, the most successful projects have a combination of quality products, trusted relationships and a team eager to be your boots on the ground. AMI provides hands-on support from experienced field teams who assist with mix design, troubleshooting and performance optimization ensuring every project gets the attention it deserves.

MORE AMI PRODUCTS



Interested in AMIBOND for your next paving project?

Reach out to your AMI representative or email marketing@asphalt-materials.com to discuss an evaluation.